


## Single Conductor Cables Insulated in 80 °C PVC Product Range: *ULPVC*



### CABLE CONSTRUCTION

1. 80 °C semi-rigid PVC insulation
2. Tinned copper core



UL FILE NO:  
**E495477**

### Characteristics

<b>Maximum Voltage:</b>	300 V <sub>ac</sub>
<b>Maximum Temperature:</b>	80 °C (@ fixed installation)
<b>Test Voltage:</b>	2000 V <sub>ac</sub>
<b>Bending Radius:</b>	≥ 8 x D

Flexform Product Code	Size Conductor [AWG]	Outer Diameter [mm]	Colour
ULPVC-80	18 AWG	1.7 ± 0.2	Optional*

\* **Colour options:** White, Black, Yellow/Green

**Style:** AWM Style 1061 VW-1

**Standard Reference:** UL 758, UL 1581, C22.2 No. 210.2-M90. Original File UL No. E132504; file CSA No. 090483

**Class:** Class I Group A FT-1

**Insulation:** 80 °C PVC insulation aver. 9 mils

Affix label here

### USE:

Internal wiring in Electric Book-keeping, Accounting, Time-Recording Machines, or Electronic Equipment if within a chassis or protected from mechanical injury.

Date: \_\_\_\_\_

*In order to improve our products, the information contained in this technical datasheet can be changed without notice. Please check periodically with our office, the date and issue number.*