


TECHNICAL DATASHEET

@ All rights reserved.

All contents of this document are our property and any copy or divulgation is not allowed without our written authorisation.

Multi Conductor Cables Insulated in PVC + PVC H03 70°C Overbraided in Metallic Braid Product Range: *BRO-Metallic Braid*



SCHEMATIC DRAWINGS

3 Core Round Construction



CABLE CONSTRUCTION

- 1. Metallic Wire Braid
- 2. 70 °C PVC inner insulation
- 3. Red copper conductor
- 4. 70 °C PVC outer insulation

APPLICATIONS

This product is designed for use as a pendant or a flexible cord for table or floor lamps, or similar light, portable apparatus, where there is a low risk of damage or mechanical abuse.


<u>Characteristics</u>		
Voltage Rating (U₀/U):	300 / 300 V _{ac}	
Working Range:	70 °C	


Size Conductor [mm²]	Conductor Stranding [Nº x mm]	Electrical Resistance [Ω/Km]
0.50	16 x 0.20	<u><</u> 39.0
0.75	24 x 0.20	<u><</u> 26.0

Revision Date:	Issue No.	Page:
23/05/2022	1.2	1 of 2

In order to improve our products, the information contained in this technical datasheet can be changed without notice. Please check periodically with our office, the date and issue











TECHNICAL DATASHEET

@ All rights reserved.

All contents of this document are our property and any copy or divulgation is not allowed without our written authorisation.

Flexform Product Code	Size Conductor [mm²]	Outer Diameter [mm]
BRO-023M	2 x 0.75	5.8 <u>+</u> 0.5
BRO-032M	3 x 0.50	5.5 <u>+</u> 0.5
BRO-033M	3 x 0.75	6.1 <u>+</u> 0.5

Cable Standards BS EN 50525-2-11:2011

BS EN 60228:2004

Low Voltage European Directive No. 2014/35/UE.

Stranding of Conductor Red copper stranded conductor

Insulation TI2 type PVC compound.

Cable Assembly The cores are twisted.

Core Identification 2 Core: Brown

Blue

3 Core: Brown 🔵 Blue 🔘 Yellow/Green 잆

Outer Sheath TM2 type PVC compound

Colour of Sheath Black or White O

Outer Braid Metallic wire braid, with an optional brass, plain copper, stainless steel, black

enamel or aged copper finish.

Please note: Due to the metallic braid, we recommend for safety purposes that this cable should always be earthed.

Revision Date: 23/05/2022

Issue No. 1.2 Page: 2 of 2

In order to improve our products, the information contained in this technical datasheet can be changed without notice. Please check periodically with our office, the date and issue number.



