


## UL Recognised Single Conductor Cables Insulated in 200 °C FEP Product Range: *ULFEP*



### CABLE CONSTRUCTION

1. 200 °C FEP insulation
2. Nickel-plated copper core



File no: E495477

### Characteristics

|                             |        |
|-----------------------------|--------|
| <b>Working Voltage:</b>     | 300V   |
| <b>Working Temperature:</b> | 200 °C |

| Flexform Product Code | Size Conductor [AWG] | Conductor Stranding [N° x mm] | Outer Diameter [mm] | Colour    |
|-----------------------|----------------------|-------------------------------|---------------------|-----------|
| ULFEP                 | 1 x 18               | 19 x 0.254                    | 1.9 ± 0.2           | Optional* |

\* Colour options: white, black, green

**In conformity to the standards:** UL 758 AWM Style 1332

**Type of conductor:** Nickel-plated copper

**Type of insulation:** 200 °C FEP insulation

**Av. insulation thickness:** 13 mils min.

**Use:** Internal wiring of appliances. Suitable for 600 Volts peak for electronic use only.

**Additional UL file numbers:** E221012, E213293



AFFIX LABEL HERE

DATE: \_\_\_\_\_

*In order to improve our products, the information contained in this technical datasheet can be changed without notice. Please check periodically with our office, the date and issue number.*